CAMRI TWO PIECE TOILET

4.8LPF / 1.28GPF OR 3LPF / 0.8GPF

□ 4720BLWU Unlined Tank with Bowl

□ 4722BLW

Bowl

□ 4721BPWU Unlined Tank

PRODUCT SPECS

- High efficiency dual flush toilet
- 4.8Lpf / 1.28Gpf or 3Lpf / 0.8Gpf
- Elongated bowl
- Vitreous china
- 15½" Bowl height
- Soft white top push button
- 12" (305mm) Rough-in
- 1¾" Fully glazed ball pass trapway
- 3" Dual flush valve
- Siphon jet flush action
- Water Surface: 8" x 6"
- (205mm x 150mm)
- Toilet seat not included

DIMENSIONS

440mm W x 740mm D x 800mm H 17¾" W x 29½" D x 31½" H

COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO cUPC - US EPA WaterSense
- ASME A112.19.2 / CSA B45.1
- MaP Premium Tested 800g
- LEED Compliant

SHIPPING

Cube 6.41 GW 86.59 lbs



TO BE SPECIFIED Colour: Soft White

NOTES: This toilet is designed to rough-in at a minimum dimension of 305mm (12") from finished wall to C/L of outlet. Supply line not included with fi ture and must be ordered separately.

Important: Dimensions of fi tures are nominal and may vary within the range of tolerances established by ASME standard A11219.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

