COLTER ELONGATED BOWL 4.2LPF / 1.1GPF

☐ 4765BEX Top Inlet

☐ 4765BEU* Rear Inlet (Special Order Only, See Price Book for Details)

PRODUCT SPECS

- High efficiency flushometer valve bowl
- 4.2Lpf / 1.1Gpf
- Will also function with 4.8Lpf / 1.28Gpf flushometer valve
- Elongated bowl
- Vitreous china
- New Pro Guard Glaze
- 15" bowl height
- 10" (254mm) Rough-in
- 2" Fully glazed ball pass trapway
- Siphon jet flush action
- 1½" NPT Top or back inlet spud
- Water surface: (240mm x 140mm) 9½" x 5½"
- Toilet seat and flushometer valve not included

DIMENSIONS

370mm W x 710mm D x 380mm H 14½" W x 28" D x 15" H

COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO cUPC
- ASME A112.19.2 / CSA B45.1
- MaP tested 1000g (Top Inlet)
- MaP tested 1000g (Rear Inlet)
- US EPA WaterSense Version 1.0

Specification

(Please note: MaP testing was completed with Sloan Flushometer Valve Model: Royal 111-1.2)

- IAPMO Green, Calgreen, and LEED Compliant

SHIPPING

Cube 3.98 GW 49.5 lbs



TO BE SPECIFIED Colour: Soft White

NOTES:

This toilet is designed to rough-in at a minimum dimension of 254mm (10") from finished wall to C/L of outlet. Flush valve not included with fixture and must be ordered separately.

Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

Bone and Biscuit available through Direct Import (CIF) only.



