## **WILTON ONE PIECE TOILET** 3.0LPF / 0.8GPF

☐ 4710BSXU **Unlined Tank** 

#### PRODUCT SPECS

- Ultra high efficiency toilet
- 3.0LPF / 0.8GPF
- Elongated bowl with concealed skirted trapway
- Vitreous China
- 161/2" Plus Height for greater comfort
- Chrome tank Lever
- 12" (305mm) Rough-in
- 2" Fully glazed ball pass trapway
- 3" Canister flush valve
- Siphon jet flush action
- Water surface: 7\%" x 5\\2" (200mm x 140mm)
- Decorative white side caps included
- Smooth close toilet seat included

#### **DIMENSIONS**

365mm W x 695mm D x 765mm H 143/8" W x 273/8" D x 301/8" H

### **COMPLIANCE CERTIFICATIONS**

Meets or exceeds the following:

- IAMPO cUPC
- US EPA WaterSense
- ASME A112.19.2 / CSA B45.1
- MaP Premium Tested 800g
- ADA Guideline & ANSI A117.1
- LEED Compliant
- OBC section 3.8 barrier free design
- CSA B651 Standard

### **SHIPPING**

Cube 7.81 GW 128 lbs



# TO BE SPECIFIED Colour: ☐ Soft White

#### NOTES:

This toilet is designed to rough-in at a minimum dimension of 305mm (12") from finished wall to C/L of outlet. Supply line not included with fixture and must be ordered separately.

Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

This toilet is designed to comply ADA and OBC barrier free requirements. It's the responsibility of installer to comply the standard prior to installation.

