

**4720FGEVU**  
**4.8 lpf / 1.28 Gpf Elongated Toilet**  
**Includes: Slow-Close Seat, Floor Bolts, and Wax Ring**

#### Specifications:

- White vitreous china
- FLUSH GUARD™ overflow protection
- Chrome tank lever
- Siphon jet flush action
- 2" Fully glazed ball pass trapway
- 3" flush valve
- 12" rough-in
- Pre-installed tank bolts for a quick connection
- Extra large footprint covers floor marks
- Works with standard plumbing; no special installation required for overflow feature
- Total package with slow-close plastic seat, wax ring, and floor bolts included
- 100% factory flush tested
- Specially designed for the use of persons who are blind or have other disabilities




#### Overall Dimensions:

440mm (W) x 760mm (D) x 763mm (H)  
 17<sup>3</sup>/<sub>8</sub>" (W) x 30" (D) x 30" (H)





#### Compliance Certifications:

- Meets or exceeds the following specs:
- IAPMO cUPC
  - ASME A112.19.2-2018/CSA B45.1-18
  - MaP tested 1000g
  - IGC 252-2018 Overflow Standard
  - Built Environment - 2020, Cal Green - 2022 and LEED® v4.1
  - EPA WaterSense Specification for Tank-Type Toilets, Version 1.2, June 2, 2014

#### FLÜSH GUARD™ ANTI-OVERFLOW TOILETS



#### EXTRA LARGE FOOTPRINT



#### Notes:

Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.